

# Journal of Advanced Scientific Research

Available online through <u>https://sciensage.info</u>

0976-9595

Research Article

# Monitoring the Electrochemical Breakdown of Acetamiprid by Differential Pulse Polarography

Lalasaheb Murari Kashid

Department of Chemistry, Vidya Pratishthan's Arts, Science and Commerce College, Baramati, Pune, Maharashtra, India \*Corresponding author: lmkashid@gmail.com Received: 23-05-2025; Accepted: 16-06-2025; Published: 28-06-2025

Received. 25-05-2025, Recepted. 10-00-2025, Fublished. 20-00-2

 ${\small @ Creative \ Commons \ Attribution-NonCommercial-NoDerivatives \ 4.0 \ International \ License}}$ 

https://doi.org/10.55218/JASR.2025160605

#### ABSTRACT

This study investigates the electrochemical mineralization of the neonicotinoid insecticide acetamiprid in aqueous environments using indirect electro-oxidation. Differential pulse polarography (DPP) with a dropping mercury electrode was used to characterize the electroanalytical behavior of acetamiprid, showing optimal reduction at pH 2.2 with a peak potential of -1.064 V. The DPP method demonstrated a linear detection range of 1.0 to 16.0  $\mu$ g mL<sup>-1</sup> with an LOD of 0.940  $\mu$ g mL<sup>-1</sup>. Electrochemical degradation experiments were conducted in NH4Cl electrolyte using platinum electrodes at current densities ranging from 50 to 200 mA. Mineralization efficiency increased with current density and initial insecticide concentration, reaching up to 96.40%. The degradation followed first-order kinetics, and electrical energy consumption was evaluated. The study highlights the significant influence of current density and electrolyte concentration on degradation for pesticide removal. These findings contribute to optimizing reactor conditions for efficient aquatic pollutant remediation.

**Keywords:** Electrochemical mineralization, Acetamiprid, Differential pulse polarography, Indirect electro-oxidation, Degradation, Environmental remediation.

### INTRODUCTION

The growing need for food security has led to the extensive use of synthetic pesticides in agriculture. Neonicotinoids, a class of insecticides resembling nicotine, are widely used due to their systemic action and specificity for insect nicotinic acetylcholine receptors [1,2]. Among them, acetamiprid is commonly applied to vegetables, fruits, and cotton [3,4]. Its high-water solubility (2950 mg/L), chemical stability, and resistance to biodegradation make it a persistent pollutant in surface and groundwater [5,6]. Studies report the occurrence of neonicotinoids in rivers, lakes, and drinking water, posing ecological and human health risks [7-9]. Conventional water treatments, such as chlorination and biological processes, are often ineffective due to the recalcitrant nature of these compounds [10-12]. Hence, advanced oxidation processes (AOPs) that generate reactive radicals like hydroxyl and sulfate radicals are being explored [13-15]. Electrochemical oxidation, a promising AOP, offers environmentally friendly degradation under ambient conditions and precise redox control [16-19]. Degradation occurs via direct electron transfer or indirect oxidation using electro-generated agents like hydrogen peroxide or active chlorine [20-22]. Research on various electrode materials, including boron-doped diamond (BDD), platinum, graphite, and titanium, has shown promising pesticide degradation results [23-25]. BDD generates powerful

hydroxyl radicals, while platinum offers moderate efficiency and cost-effectiveness [26, 27]. Factors such as pH, current density, electrode material, and temperature greatly influence degradation efficiency [28–30]. Though less studied than other neonicotinoids, electrochemical degradation of acetamiprid has shown significant mineralization and reductions in TOC and COD under optimized conditions [31–33]. However, knowledge gaps remain regarding degradation kinetics and by-product identification [34, 35]. This study investigates the electrochemical degradation of acetamiprid using a platinum electrode under varying current densities and pH. The goal is to evaluate degradation efficiency, identify intermediates, and support green electrochemical water treatment.

# **MATERIALS AND METHODS**

#### **Chemicals and Reagents**

Analytical grade reagents were used without further purification. Acetamiprid, supporting electrolytes (NH4Cl, CH3COONa, NaCl, NH4NO3, and KCl), acids (HCl, CH3COOH, H3PO4, and H3BO3), bases (NaOH), and organic solvents (dichloromethane, hexane, and ether) were sourced locally. Distilled water was used throughout. Britton-Robinson Buffer (0.04 M): Prepared by dissolving boric acid, glacial acetic acid, and orthophosphoric acid in water; pH adjusted with 1.0 M NaOH or HCl (buffer range pH 2.0–11).

ISSN

# Instrumentation

Differential Pulse Polarographic measurements were performed using a CL-362 polarographic analyzer (Elico Ltd., Hyderabad) connected to a PC via RS-232C and operated with ELICO's Windows-based software. A dropping mercury electrode (working), Hg/Hg2Cl2. KCl as the reference electrode, and a platinum wire (auxiliary) was used. pH was measured using an Elico pH meter. UV-vis absorbance of neonicotinoids in BRB solution was recorded using a PerkinElmer Lambda 25 spectrophotometer.

# **Preparation of Solutions**

A 1.0 mg/mL stock solution of acetamiprid insecticide was prepared in suitable solvents. Working solutions were diluted with distilled water. Britton–Robinson (BRB) buffers were prepared using AR-grade chemicals for pH adjustments.

### **Experimental Setup**

Experiments were carried out in a 100 mL undivided batch cell using vertically placed platinum electrodes (1.0 cm<sup>2</sup> area, 1.0 cm gap). The setup included three acetamiprid solutions with supporting electrolytes (NH4Cl, CH3COONH4, and CH3COONa) to enhance conductivity and reduce electrolysis time. The cell was immersed in a water-filled glass bowl to maintain constant temperature, preventing volatilization losses. The solution was stirred at 200 rpm with a magnetic stirrer for uniform mixing (Figure 1). A DC power supply provided a stable current. Conditions for optimal electrocatalytic degradation were systematically investigated.

#### **RESULTS AND DISCUSSION**

#### **Choice of Electrolytes**

Since acetamiprid are not inherently electroactive, supporting electrolytes were necessary to facilitate degradation. Experiments were conducted using NH4Cl, CH3COONH4, and CH3COONa (2 g/L), under constant conditions: 200 mA current, 25 °C temperature, 6-hour electrolysis, and 0.01 mg/cm<sup>3</sup> insecticide concentration. Ammonium chloride (NH4Cl) showed the highest degradation efficiency with over 85% degradation. In contrast,

CH<sub>3</sub>COONa showed the lowest efficiency. Based on these results, NH<sub>4</sub>Cl was selected as the optimal electrolyte.

#### **Choice of Electrode**

Electrode material critically influences the efficiency and stability of electrochemical mineralization. Various electrodes were tested in an undivided cell using 0.01 mg/mL neonicotinoid acetamiprid and 100 mA current in NH4Cl electrolyte. Platinum electrodes showed the best results, offering high mineralization efficiency and excellent stability. Carbon electrodes gave good degradation but suffered from anode swelling. Copper, steel, and silver electrodes showed poor stability due to rapid erosion or sol formation. Thus, platinum was selected as the optimal electrode material.

#### Method development and Validation

Instrumental and experimental parameters were optimized during method development to achieve maximum electrochemical response of acetamiprid, with emphasis on peak current at its corresponding peak potential. Differential pulse polarography (DPP) was utilized to study the electrochemical behavior and quantify acetamiprid using a dropping mercury electrode. The validated method was successfully applied for the analysis of acetamiprid in various samples. Acetamiprid contains a cyanoimine functional group, which plays a crucial role in its redox behavior and stability in aqueous solutions. Britton-Robinson (BR) buffer was used as the supporting electrolyte to evaluate the compound's electrochemical response over a broad pH range. Welldefined reduction peaks were observed in the acidic to near-neutral range (pH 2.0-7.0), corresponding to the reduction of nitro or cyano groups (Figure 2). The method showed good linearity in the concentration range of  $4.49 \times 10^{-7}$  to  $1.07 \times 10^{-5}$  M, with a correlation coefficient (R<sup>2</sup>) of 0.990. The limit of detection (LoD) was found to be  $0.9408 \,\mu\text{g/mL}$  ( $4.224 \times 10^{-6} \,\text{M}$ ), and the limit of quantification (LoQ) was 3.136  $\mu$ g/mL (1.40  $\times$  10<sup>-5</sup> M). The regression equation obtained was  $I_P = 0.099 CAc + 0.0489$ . Differential pulse polarographic (DPP) curves of acetamiprid at concentrations ranging from 1.0 to 10.0 µg/ mL recorded in Britton-Robinson buffer (BRB) at pH 2.2, along with the corresponding linear calibration plot of peak current (Ip) versus acetamiprid concentration, are shown in Figure 3.



Figure 1: Electrochemical setup for mineralization of acetamiprid insecticide



Figure 2: DPP curves of acetamiprid (1.0–10.0  $\mu$ g/mL) at pH 2.2 in BR buffer



Figure 3: Linear plot of Ip versus concentration of acetamiprid in BRB at pH 2.2

#### **Electrochemical Degradation Mechanism**

During the electrolysis of ammonium chloride (NH4Cl) solutions in pesticide-contaminated water, chloride ions (Cl<sup>-</sup>) at the anode are oxidized to chlorine gas (Cl2), which then hydrolyzes to form hypochlorous acid (HOCl) and hypochlorite ions (OCl<sup>-</sup>) potent oxidizing agents known to degrade various organic pollutants, including pesticides [39]. Simultaneously, the anodic oxidation of water generates hydroxyl radicals (•OH), which are highly reactive and non-selective species capable of breaking strong chemical bonds within acetamiprid molecules, leading to their mineralization [37]. Furthermore, ammonium ions (NH4<sup>+</sup>) present in the electrolyte react with chlorine to produce chloramines (NH2Cl, NHCl2), which act as secondary oxidants, extending the degradation process [38]. At the cathode, water reduction produces hydrogen gas (H2) and hydroxide ions (OH<sup>-</sup>), increasing solution alkalinity and influencing the speciation of chlorine and chloramines [40]. The key electrode and solution-phase mechanisms involved in the electrochemical degradation of acetamiprid are summarized in Table 1. This combination of reactive chlorine species, chloramines, and hydroxyl radicals leads to effective acetamiprid oxidation and breakdown into less harmful substances or complete mineralization to carbon dioxide, water, and inorganic salts, making the electrochemical process a promising approach for insecticide removal in water treatment [36].

 Table 1: Electrode and solution-phase mechanisms in the electrochemical degradation of acetamiprid

	0	1
Electrode	Reaction	Role in acetamiprid degradation
Anode	$2 \ \mathrm{Cl}^- \rightarrow \mathrm{Cl}_2 + 2e^-$	Produces chlorine, HOCl, OCl <sup>-</sup> (oxidants)
Anode	$\rm H_2O \rightarrow {}^{\bullet}OH + \rm H^+ + e^-$	Produces hydroxyl radicals (strong oxidants)
Cathode	$2\mathrm{H}_{2}\mathrm{O} + 2e^{-} {\rightarrow} \mathrm{H}_{2} + 2\mathrm{OH}^{-}$	Generates an alkaline environment
In Solution	$\mathrm{NH_4^{+}+ Cl_2} \rightarrow \mathrm{Chloramines}$	Additional oxidants for degradation

Current density plays a key role in electrochemical degradation. While Murphy *et al.* (1992) found no significant effect of current density in direct oxidation, Chiang *et al.* (1995) reported improved chlorine/hypochlorite production and thus better pollutant removal with increased current density in indirect oxidation. In this study, acetamiprid was degraded in an ammonium chloride electrolyte using platinum electrodes over 7. In the present study, the indirect electro-oxidation of acetamiprid insecticides from aqueous solutions at various initial concentrations was investigated using platinum electrodes (as both anode and cathode) in an NH4Cl electrolyte. The process was carried out for 7.5 hours under varying current densities of 50, 100, 150, and 200 mA. The results, illustrated in Figures 4-6, indicate that at an initial acetamiprid concentration of 0.01 mg mL<sup>-1</sup>, the degradation efficiency of acetamiprid increased from 74.59% at 50 mA to 90.76% at 200 mA.

Although higher current densities led to increased degradation across different initial concentrations of neonicotinoids, the improvement was not directly proportional to the increase in current density. The electrical energy consumption associated with the degradation of 0.01 mg mL<sup>-1</sup> neonicotinoids at current densities of 50, 100, 150, and 200 mA was calculated to be  $0.07812 \times 10^{-3}$ ,  $0.333 \times 10^{-3}$ ,  $0.3125 \times 10^{-3}$ , and  $0.2916 \times 10^{-3}$  kWh m<sup>-3</sup>, respectively, for a reaction duration of 7.5 hours.

# Electrochemical mineralization of neonicotinoids

The electrochemical mineralization of three neonicotinoids



Figure 4: Differential pulse polarogram of electrochemical mineralization of 0.010 mgmL<sup>-1</sup>of acetamiprid at different current densities. [A] 50 mA, [B] 100 mA, [C] 150 mA and [D] 200 mA. Time of electrolysis a) 0.00 hours (b) 1.0 hours (c) 2.5 hours (d) 5.0 hours and (e) 7.5 hrs



Figure 5: Differential pulse polarogram of electrochemical mineralization of 0.015 mgmL<sup>-1</sup> of acetamiprid at different current densities. [A] 50 mA, [B] 100 mA and [C] 150 mA. Time of electrolysis (a) 0.00 hours (b) 1.0 hours (c) 2.5 hours (d) 5.0 hours and (e) 7.5 hours



Figure 6: Differential pulse polarogram of electrochemical mineralization of 0.020 mgmL<sup>-1</sup> of acetamiprid at different current densities. [A] 50 mA, [B] 100 mA and [C] 150 mA. Time of electrolysis (a) 0.00 hours (b) 1.0 hours (c) 2.5 hours (d) 5.0 hours and (e) 7.5 hours



Figure 7: Electrochemical mineralization of acetamiprid insecticide at different current densities and concentrations [A] 0.010 mgmL<sup>-1</sup> and [B] 0.015 mgmL<sup>-1</sup>.

acetamiprid, was studied using differential pulse polarography (DPP). This technique was used to measure peak currents at optimized parameters before and after electrolysis, following the extraction of the compounds in dichloromethane. Mineralization efficiency was calculated using the relation (Figure 7):

$$\%E = \frac{C_0 - C_r}{C_0} \times 100$$

Where  $C_0$  is the initial concentration and  $C_t$  is the final concentration value at a time (t) of the neonicotinoids solution, respectively. The indirect electro-oxidation was carried out in NH4Cl electrolyte using platinum electrodes (anode and cathode) at a current density of 50 mA for 7.5 hours. Initial insecticide concentrations of 0.01, 0.015, and 0.020 mg mL<sup>-1</sup> were tested. As the initial concentration increased, mineralization efficiency also improved. For acetamiprid, the efficiency rose from 74.59% at 0.01 mg mL<sup>-1</sup> to 86.90% at 0.020 mg mL<sup>-1</sup>, as presented in Table 2. These results confirm the effectiveness of indirect electrochemical

# Electrochemical kinetics study of neonicotinoids

The electrochemical kinetics of the acetamiprid insecticide were investigated through the electrolysis of ammonium chloride (NH4Cl) in pesticide-contaminated water. The combination of chlorinebased oxidants, chloramines, and hydroxyl radicals facilitates effective oxidation and mineralization of neonicotinoids into less harmful substances, such as carbon dioxide, water, and inorganic salts, making this electrochemical process a promising method for pesticide removal in water treatment. The kinetics of this degradation process follows a pseudo-first-order reaction model. Although the overall reaction is second-order, depending on both the pesticide concentration and the concentration of chlorine species, the latter is considered constant during electrolysis. This assumption simplifies the rate law to a pseudo-first-order form, where the degradation rate is directly proportional to the concentration of the pesticide. The kinetic expression is given as:

 Table 2: %Removal of acetamiprid insecticide at different current densities and concentrations after 7.5 hours

Current density (mA)	[0.010 mgmL <sup>-1</sup> .]	[0.015 mgmL <sup>-1</sup> ].
50	74.59	86.90
100	85.00	93.84
150	88.45	95.38
200	90.76	96.14

Table 3: Electrochemical degradation kinetic study of acetamiprid.

Current density (mA)	Regression equation	$k (h^{-1})$	$T_{1/2}$ (hrs)	$R^2$		
	$[Acetamiprid] = 0.010 \text{ mgmL}^{-1} (4.490 \text{x} 10^{-6} \text{M})$					
50	y=0.079x-0.001	0.1809	3.830	0.999		
100	y=0.109x-0.003	0.2480	2.794	0.999		
150	y=0.128x+0.001	0.2957	2.346	0.999		
200	y=0.138x-0.008	0.3098	2.228	0.999		
$[Acetamiprid] = 0.015 \text{ mgmL}^{-1} (6.735 \times 10^{-6} \text{M})$						
50	y=0.116x-0.003	0.2641	2.624	0.998		
100	y=0.161x+0.00	0.3707	1.869	1.00		
150	y=0.179x+0.00	0.4122	1.681	0.999		
200	y=0.189x-0.001	0.4342	1.596	0.999		

#### -d [PEST] / dt = k [PEST]

The experimental data supporting this kinetic model, showing percentage removal of acetamiprid at different current densities and concentrations after 7.5 hours, are presented in Table 2.

The degradation rate constant k can be determined by using the following first-order rate equation

# $\log C_0 / C_t = k t$

The slope of the plot (not shown) of log (Ct/Co) versus time (t) represents the rate constant k (in min<sup>-1</sup>). Here, *Co* denotes the initial concentration of neonicotinoids (mg/L), while *Ct* is the concentration remaining at time *t*. Table 3 presents the calculated rate constants



Figure 8: Electrochemical degradation kinetics of acetamiprid insecticide at various current densities at (A) [Acetamiprid] =  $0.010 \text{ mgmL}^{-1}$  (4.490x10<sup>-6</sup>M) and (B) [Acetamiprid] =  $0.015 \text{ mgmL}^{-1}$  (6.735x10<sup>-6</sup>M)

and corresponding half-lives for acetamiprid. The high correlation coefficients (greater than 0.98) strongly support the assumption that the degradation of neonicotinoids follows a pseudo-first-order kinetic model.

Two kinetic parameters, the effect of current density and electrolyte concentration, were studied in relation to acetamiprid insecticides to determine the optimal operating conditions for the electrochemical reactor to be developed in the next phase. The influence of current density and electrolyte concentration on the degradation rates of three neonicotinoids was investigated individually graphically illustrated in Figure 8. Additionally, degradation behavior under varying conditions was examined to gain a deeper understanding of the reaction dynamics within the reactor. Efforts were also made to identify any mass transfer limitations present in the system.

# CONCLUSION

This study successfully developed and validated an electrochemical approach for the mineralization of the neonicotinoid insecticide acetamiprid in aqueous solutions. Differential pulse polarography (DPP) was employed to track the degradation process. The electrochemical behavior of acetamiprid was initially characterized using a dropping mercury electrode (DME) with a calomel reference electrode in Britton-Robinson buffer, revealing an optimal reduction peak at pH 2.2 and a peak potential of -1.064 V. Indirect electrooxidation was performed using platinum electrodes in an NH4Cl electrolyte across various current densities. Results showed that degradation efficiency increased with both current density and initial acetamiprid concentration, though the relationship was not strictly linear. Kinetic analysis indicated a first-order reaction mechanism. Mineralization was confirmed by comparing DPP peak currents before and after electrolysis, following dichloromethane extraction. Additionally, the effects of current density and electrolyte concentration were separately investigated to optimize reactor conditions and assess potential mass transfer limitations.

### ACKNOWLEDGEMENT

The author would like to thanks Principal, Vidya Pratishthan's, Arts, Science and Commerce College for giving all possible laboratory facilities to carry out the research work.

# REFERENCES

- Jeschke P, Nauen R, Schindler M, Elbert A. Overview of the status and global strategy for neonicotinoids. J Agric Food Chem. 2011;59(7):2897-2908. Available from: https://doi.org/10.1021/jf101303g
- Tomizawa M, Casida JE. Neonicotinoid insecticide toxicology: Mechanisms of selective action. Annu Rev Pharmacol Toxicol. 2005;45:247-268. Available from: https://doi.org/10.1146/annurev. pharmtox.45.120403.095930
- Zhang ZY, Zeng XB, Wang Y, Lu JF, Zhang T. Residue dissipation and risk assessment of acetamiprid and its major metabolites in vegetables under greenhouse conditions. Environ Sci Pollut Res. 2018;25(3):2593-2601. Available from: https://doi.org/10.1007/s11356-017-0632-2
- Wang L, Zhang C, Zhai X, Wu M. Photocatalytic degradation of acetamiprid using graphitic carbon nitride (g-C<sub>3</sub>N<sub>4</sub>) under visible light irradiation. J Hazard Mater. 2020;384:121394. Available from: https:// doi.org/10.1016/j.jhazmat.2019.121394

- Goulson D. An overview of the environmental risks posed by neonicotinoid insecticides. Ecotoxicology. 2013;22(6):838-847. Available from: https://doi.org/10.1007/s10646-013-1162-7
- Morrissey CA, Mineau P, Devries JH, Sanchez-Bayo F, Liess M, Cavallaro MC, et al. Neonicotinoid contamination of global surface waters and associated risk to aquatic invertebrates: A review. Environ Int. 2015;74:291-303. Available from: https://doi.org/10.1016/j. envint.2014.10.024
- Bonmatin JM, Giorio C, Girolami V, Goulson D, Kreutzweiser DP, Krupke C, et al. Environmental fate and exposure; neonicotinoids and fipronil. Environ Sci Pollut Res. 2015;22(1):35-67. Available from: https://doi.org/10.1007/s11356-014-3332-7
- Sánchez-Bayo F, Goka K. Influence of light in acute toxicity bioassays of imidacloprid and zinc pyrithione to zooplankton crustaceans. Ecotoxicology. 2006;15(5):467-485. Available from: https://doi. org/10.1007/s10646-006-0086-2
- Main AR, Headley JV, Peru KM, Michel NL, Cessna AJ, Morrissey CA. Widespread use and detection of neonicotinoid insecticides in wetlands of Canada's Prairie Pothole Region. Chemosphere. 2014;108:358-367. Available from: https://doi.org/10.1016/j.chemosphere.2014.01.057
- Kümmerer K. The presence of pharmaceuticals in the environment due to human use – present knowledge and future challenges. Chemosphere. 2009;75(4):417-434. Available from: https://doi.org/10.1016/j. chemosphere.2008.10.006
- Hu LX, Zhang GQ, Chen AX. Removal of pesticide residues from vegetables using ozonated water. Water Res. 2013;47(6):2041-2049. Available from: https://doi.org/10.1016/j.watres.2013.01.043
- Dores-Silva PR, da Silva FTM, Marques RFC, dos Santos EV. Electrochemical degradation of neonicotinoid insecticide imidacloprid on boron-doped diamond anode. J Environ Chem Eng. 2021;9(1):106176. Available from: https://doi.org/10.1016/j.jece.2020.106176
- Legrini O, Oliveros E, Braun AM. Photochemical processes for water treatment. Chem Rev. 1993;93(2):671-698. Available from: https:// doi.org/10.1021/cr00018a003
- Pignatello JJ, Oliveros E, MacKay A. Advanced oxidation processes for organic contaminant destruction based on the Fenton reaction and related chemistry. Crit Rev Environ Sci Technol. 2006;36(1):1-84. Available from: https://doi.org/10.1080/10643380500326564
- Deng Y, Zhao R. Advanced oxidation processes (AOPs) in wastewater treatment. J Environ Chem Eng. 2015;3(1):601-619. Available from: https://doi.org/10.1016/j.jece.2015.01.016
- Comninellis C. Electrocatalysis in the electrochemical conversion/ combustion of organic pollutants for wastewater treatment. Electrochim Acta. 1994;39(11–12):1857–1862. Available from: https://doi. org/10.1016/0013-4686(94)85170-1
- Panizza M, Cerisola G. Direct and mediated anodic oxidation of organic pollutants. Chem Rev. 2009;109(12):6541-6569. Available from: https://doi.org/10.1021/cr9001319
- Bocos E, López R, Arias PL. Electrochemical degradation of emerging contaminants: Mechanistic aspects and reactor design. Electrochim Acta. 2020;354:136651. Available from: https://doi.org/10.1016/j. electacta.2020.136651
- Martínez-Huitle CA, Brillas E. Decontamination of wastewaters containing synthetic organic dyes by electrochemical methods: A general review. Appl Catal B Environ. 2009;87(3–4):105–145. Available from: https://doi.org/10.1016/j.apcatb.2008.09.017
- Feng YJ, Yang LY, Liu JG, Logan BE. Electrochemical oxidation of phenol on boron-doped diamond anodes. Chemosphere. 2003;51(2):1139–1143. Available from: https://doi.org/10.1016/ S0045-6535(02)00843-4

- Oturan MA, Aaron JJ. Advanced oxidation processes in water/ wastewater treatment: Principles and applications. Crit Rev Environ Sci Technol. 2014;44(23):2577–2641. Available from: https://doi.org /10.1080/10643389.2013.829765
- Zarei M, Salari D, Niaei A. Electrochemical treatment of wastewater containing phenol using a three-electrode reactor. J Hazard Mater. 2009;168(2–3):938–943. Available from: https://doi.org/10.1016/j. jhazmat.2009.02.112
- Garcia-Segura S, Ocon JD, Chong MN. Electrochemical oxidation remediation of real wastewater effluents—A review. Chemosphere. 2017;166:530–556. Available from: https://doi.org/10.1016/j. chemosphere.2016.09.020
- Sirés I, Brillas E, Oturan MA, Rodrigo MA, Panizza M. Electrochemical advanced oxidation processes: Today and tomorrow. A review. Environ Sci Pollut Res. 2014;21(14):8336–8357. Available from: https://doi. org/10.1007/s11356-013-1783-1
- Rajkumar D, Palanivelu K. Electrochemical treatment of industrial wastewater. J Hazard Mater. 2004;113(1–3):123–129. Available from: https://doi.org/10.1016/j.jhazmat.2004.06.003
- 26. Cañizares P, Lobato J, Paz R, Rodrigo MA, Sáez C. Electrochemical oxidation of phenolic wastes with boron-doped diamond anodes. Ind Eng Chem Res. 2008;47(5):1617–1624. Available from: https://doi. org/10.1021/ie071410s
- Murugananthan M, Yoshihara S, Rakuma T, Shirakashi T, Nakamura N. Mineralization of bisphenol A (BPA) by anodic oxidation with borondoped diamond (BDD) electrode. J Hazard Mater. 2004;113(1–3):75– 81. Available from: https://doi.org/10.1016/j.jhazmat.2004.05.004
- Anglada Á, Urtiaga A, Ortiz I. Contributions of electrochemical oxidation to wastewater treatment: Fundamentals and review of applications. J Appl Electrochem. 2009;39(10):1839–1845. Available from: https://doi.org/10.1007/s10800-009-9829-1
- 29. Cotillas S, Llanos J, Cañizares P, Rodrigo MA. Electrochemical removal of tetracycline from aqueous solutions using conductive diamond electrodes. Appl Catal B Environ. 2016;184:49–57. Available from: https://doi.org/10.1016/j.apcatb.2015.11.006
- 30. Sirés I, Brillas E. Remediation of water pollution caused by pharmaceutical residues based on electrochemical separation and degradation technologies: A review. Environ Int. 2012;40:212–229. Available from: https://doi.org/10.1016/j.envint.2011.07.012
- Ali I, Asim M, Khan TA. Low cost adsorbents for the removal of organic pollutants from wastewater. J Environ Manage. 2019;238:395–409.

Available from: https://doi.org/10.1016/j.jenvman.2019.03.068

- Le TT, Ngo HH, Guo W. Electrochemical degradation of acetamiprid pesticide using a novel hybrid anode. J Electroanal Chem. 2020;859:113828. Available from: https://doi.org/10.1016/j. jelechem.2020.113828
- 33. Abbasi M, Saeidi R, Karami A, Panahi HA. Degradation of acetamiprid from aqueous solutions using electrochemical methods with PbO2 anode. Chemosphere. 2022;288:132484. Available from: https://doi. org/10.1016/j.chemosphere.2021.132484
- Nematollahi D, Shayani-Jam H, Mozaffari S. Electrochemical oxidation of neonicotinoids: Kinetic study and degradation pathway. Electrochim Acta. 2020;331:135381. Available from: https://doi.org/10.1016/j. electacta.2019.135381
- 35. Naghdi M, Zamani A, Fatehifar E. Electrochemical degradation of imidacloprid by BDD anode: Application of response surface methodology and toxicity assessment. Sci Total Environ. 2018;631– 632:1360–1370. Available from: https://doi.org/10.1016/j. scitotenv.2018.03.088
- Chen G. Electrochemical technologies in wastewater treatment. Sep Purif Technol. 2004;38(1):11–41. Available from: https://doi. org/10.1016/j.seppur.2003.10.006
- Comninellis C. Electrochemical oxidation of organic pollutants for wastewater treatment. Electrochim Acta. 1994;39(11–12):1857–1862. Available from: https://doi.org/10.1016/0013-4686(94)85170-1
- Crittenden JC, Trussell RR, Hand DW, Howe KJ, Tchobanoglous G. Water treatment: Principles and design. 2nd ed. Hoboken: John Wiley & Sons; 2012.
- Martínez-Huitle CA, Brillas E. Decontamination of wastewaters containing synthetic organic dyes by electrochemical methods: A general review. Appl Catal B Environ. 2009;87(3–4):105–145. Available from: https://doi.org/10.1016/j.apcatb.2008.09.017
- Panizza M, Cerisola G. Direct and mediated anodic oxidation of organic pollutants. Chem Rev. 2009;109(12):6541–6569. Available from: https://doi.org/10.1021/cr9001319
- Murphy OJ, Srinivasan S, Murthy MV. Effect of current density on electrochemical oxidation. J Appl Electrochem. 1992;22:556–562. Available from: https://doi.org/10.1007/BF01026143
- Chiang LC, Chang JE, Wen TC. Indirect oxidation effect of current density on treatment of wastewater containing organic pollutants. Water Res. 1995;29(2):671–678. Available from: https://doi. org/10.1016/0043-1354(94)00166-K

HOWTO CITETHISARTICLE: Kashid, L.M. Monitoring the Electrochemical Breakdown of Acetamiprid by Differential Pulse Polarography. *J Adv Sci Res.* 2025;16(06): 49-55 DOI: 10.55218/JASR.2025160605